

Peli protector cases – Protector case – 1150 case



1150 Case

Interior dimensions:

20.8 x 14.4 x 9.2 cm
(8.18" x 5.68" x 3.62")

- Watertight, crushproof, and dust proof
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditionally Guaranteed



Configurations

Cat. #	Description
1150	1150 Case (with foam)
1150NF	1150 Case (no foam)



Black



Silver



Orange



Yellow

1150 Case Specifications

Exterior Dimensions (L x W x D) 23.2 x 19.2 x 11.1 cm (9.12" x 7.56" x 4.37")	Interior Dimensions (L x W x D) 20.8 x 14.4 x 9.2 cm (8.18" x 5.68" x 3.62")	
Lid Depth 1.9 cm (0.75")	Bottom Depth 7.3 cm (2.87")	Total Depth 9.2 cm (3.62")
Weight w/Foam 0.9 kg. (1.98 lbs)	Weight w/o Foam 0.8kg (1.76 lbs.)	Buoyancy Max. 3.63 kg (8 lbs.)
Range Temperature -23 / 99° C (-10 / 210° F)		

1150 Case Certificates

- IP67(1 meter submersion for 30 minutes) • Def Stan 81-41/STANAG 4280

1150 Case Accessories

Cat. #	Description
1150PF	Special Application Panel Frame
1151	3 pc. Replacement Foam Set