

# Peli protector cases – Total protection box – 1630 Transport Case



## 1630 Transport Case

### Interior dimensions:

70.3 x 53.3 x 39.4 cm  
(27.70" x 20.98" x 15.50" )

**This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application**

- **Watertight, crushproof, and dust proof**
- Easy-open, double-step latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 3 layer Pick 'N' Pluck™ foam with convoluted lid foam
- Personalised nameplate service available
- Unconditionally Guaranteed
- **Retractable extension handle**
- **Strong polyurethane wheels with stainless steel bearings**



Black

## Configurations

### Cat. # Description

1630 1630 Transport Case (with foam)

1630NF1630 Transport Case (no foam)

1634 1630 Transport Case with Padded Dividers

## 1630 Transport Case Specifications

### Exterior Dimensions (L x W x D)

79.4 x 61.5 x 44.4 cm  
(31.28" x 24.21" x 17.48")

### Interior Dimensions (L x W x D)

70.3 x 53.3 x 39.4 cm  
(27.70" x 20.98" x 15.50")

**This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.**

### Lid Depth

8.3 cm  
(3.25")

### Bottom Depth

30.8 cm  
(12.14")

### Total Depth

39.4 cm  
(15.50")

### Weight w/Foam

16.33 kg.  
(36 lbs)

### Weight w/o Foam

14.06kg  
(31 lbs.)

### Buoyancy Max.

158.76 kg  
(350 lbs. )

### Range Temperature

-23 / 99° C  
(-10 / 210° F)

### No. of Wheels

4

Personalized Nameplate Available

## 1630 Transport Case Certificates

- IP67(1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

## 1630 Transport Case Accessories

Cat. #	Description
1631	5 pc. Replacement Foam Set