

Peli protector cases – Protection transport cases – 1660 case



1660 Case

Interior dimensions:

71.5 x 50.1 x 44.7 cm
(28.18" x 19.75" x 17.62")

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application

- **Watertight, crushproof, and dust proof**
- Easy-open, double-step latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Large, fold-down handles for 2 person lift
- Stainless steel hardware and padlock protectors
- 3 layer Pick 'N' Pluck™ foam with convoluted lid foam
- Personalised nameplate service available
- Unconditionally Guaranteed
- **Retractable extension handle**
- **4 strong polyurethane wheels with stainless steel bearings**



Black

Configurations

Cat. #	Description
1660	1660 Case (with foam)
1660NF	1660 Case (no foam)
1664	1660 Case with Padded Dividers

1660 Case Specifications

Exterior Dimensions (L x W x D)

80 x 58.1 x 48.2 cm
(31.50" x 22.87" x 19.00")

Interior Dimensions (L x W x D)

71.5 x 50.1 x 44.7 cm
(28.18" x 19.75" x 17.62")

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Lid Depth

8.9 cm
(3.50")

Bottom Depth

35.9 cm
(14.12")

Total Depth

44.7 cm
(17.62")

Weight w/Foam

19.1 kg.
(42.11 lbs)

Weight w/o Foam

15.5kg
(34.17 lbs.)

Buoyancy Max.

158.8 kg
(350.1 lbs.)

Range Temperature

-23 / 99° C
(-10 / 210° F)

No. of Wheels

4

Personalized Nameplate Available

1660 Case Certificates

- IP67(1 meter submersion for 30 minutes) • Def Stan 81-41/STANAG 4280

1660 Case Accessories

Cat. #	Description
1661	5 pc. Replacement Foam Set
1665	Padded Divider Set Only
1669	Photo/Lid Organizer for 1660 Case